## NSN 5935-01-549-5019

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-549-5019

**Body Style:** 

Straight shape, external coupling

**Overall Length:** 

33.6 millimeters

**Overall Height:** 

33.3 millimeters

**Overall Width:** 

33.3 millimeters

#### **Environmental Protection:**

Corrosion resistant and fungus resistant and moisture resistant and salt spray proof and shock resistant and vibration resistant and weather resistant

#### Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 24.6 millimeters and 26.9 millimeters

#### Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 24.6 millimeters and 26.9 millimeters

#### **Distance From Mounting Shoulder To Front Face:**

20.8 millimeters

#### **Threaded Device Type:**

Back shell and coupling facility

#### **Mating End Quantity:**

1

#### **Contact Position Arrangement Style:**

17-26 single mating end

#### **Polarization Method:**

Keyway or multiple keyway

### **Insert Position In Deg:**

0.0 and 50.0 and 160.0 and 190.0 and 225.0

#### Shell Type:

Solid

#### **Connector Locking Method:**

Externally threaded shell

#### **Terminal Location:**

Back single mating end single contact grouping

#### **Terminal Type:**

Crimp single mating end single contact grouping

#### **Shell Material:**

Aluminum alloy

#### **Shell Surface Treatment:**

Cadmium

## **Included Contact Quantity:**

26 single mating end single contact grouping

## **Included Contact Type:**

Round socket single mating end single contact grouping

# NSN 5935-01-549-5019

Electrical Receptacle Connector - Page 2 of 2



Special	Features:
---------	-----------

Contacts per mil-c-39029/56-351; 1500-cycle socket contacts

**Precious Material And Location:** 

Contact surfaces gold

Precious Material:

Gold

#### **Test Data Document:**

81349-mil-dtl-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Specification Data:**

81349 - mil-dtl-38999/20 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A039b0