Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-549-5666

### Body Style:

Straight shape, external coupling

### **Overall Length:**

33.6 millimeters

# **Overall Height:**

33.3 millimeters

# **Overall Width:**

33.3 millimeters

### **Environmental Protection:**

Corrosion resistant and fungus resistant and moisture resistant and salt spray proof and shock resistant and vibration resistant and weather resistant

### Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 24.6 millimeters and 26.9 millimeters

### Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 24.6 millimeters and 26.9 millimeters

# Distance From Mounting Shoulder To Front Face:

20.8 millimeters

### Threaded Device Type:

Back shell and coupling facility

#### Mating End Quantity:

1

### **Contact Position Arrangement Style:**

17-26 single mating end

#### **Polarization Method:**

Keyway or multiple keyway

#### **Insert Position In Deg:**

0.0 and 50.0 and 160.0 and 190.0 and 225.0

#### Shell Type:

Solid

#### **Connector Locking Method:**

Externally threaded shell

#### **Terminal Location:**

Back single mating end single contact grouping

#### **Terminal Type:**

Crimp single mating end single contact grouping

#### **Shell Material:**

Aluminum alloy

### Shell Surface Treatment:

Cadmium

#### **Included Contact Quantity:**

26 single mating end single contact grouping

# Included Contact Type:

Round pin single mating end single contact grouping



### **Special Features:**

Contacts per mil-c-39029/58-363; 1500-cycle pin contacts

**Precious Material And Location:** 

Contact surfaces gold

Precious Material:

Gold

# Test Data Document:

81349-mil-dtl-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Specification Data:**

81349 - mil-dtl-38999/20 government specification

**Shelf Life:** N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0