

View Online at <https://aerobasegroup.com/nsn/5935-01-552-4360>

Body Style:

Straight shape, internal coupling

Overall Length:

1.593 inches

Overall Diameter:

0.750 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

Tnc single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Frequency Rating:

11.0 gigahertz single mating end single contact grouping

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Contact Surface Treatment Specification:

Astm b488, type 2, code c, cl 1.27 assn standard all treatment responses single mating end single contact grouping and ams-qq-n-290, cl1 assn standard all treatment responses single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Contact Material Specification:

Astm b194 assn standard single material response single mating end single contact grouping or astm b196 assn standard single material response single mating end single contact grouping or astm b197 assn standard single material response single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Silver

Shell Surface Treatment Specification:

Astm b700 assn standard single treatment response

Shell Material Specification:

Astm b16 assn standard single material response or astm b36 assn standard single material response or astm b121 assn standard single material response

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial socket single mating end single contact grouping

Precious Material And Location:

Precious Material:

Gold and silver

Test Data Document:

81349-mil-prf-39012 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-prf-39012 spec.