## NSN 5935-01-560-6955

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-560-6955

**Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape threaded **Overall Length:** 1.570 inches **Overall Diameter:** 1.250 inches **Unthreaded Mounting Hole Diameter:** Between 0.880 inches and 0.890 inches **Distance From Mounting Shoulder To Front Face:** 1.390 inches **Mounting Facility Thickness:** 0.500 inches **Threaded Device Type:** Coupling facility and mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** 13-oct single mating end **Polarization Method:** Key, multiple key groove **Insert Position In Deg:** 90.0 **Connector Locking Method:** Externally threaded shell **End Application:** An/wld-1 (v) remote mine hunting system **Operating Tempurature Rating:** Between -55.0 degrees celsius and 125.0 degrees celsius **Features Provided:** Color band engagement indicator **Thread Size:** 0.750 inches and 0.875 inches **Terminal Location:** Back single mating end single contact grouping

Conner single matin

Copper single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

## NSN 5935-01-560-6955

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Stainless steel
Shell Surface Treatment:
Passivate
Included Contact Quantity:
13 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round w/flat
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact plating gold
Precious Material:
Gold
Thread Series Designator:
Special acme and unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0