

View Online at <https://aerobasegroup.com/nsn/5935-01-560-8890>

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Straight shape, internal coupling

Overall Length:

1.234 inches

Environmental Protection:

Fungus resistant and humidity resistant and oil resistant and solvent resistant and thermal shock resistant and vibration resistant and moisture proof and salt water resistant and vibration proof and corrosion resistant and dust resistant and fuel resistant

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

25-29 single mating end

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Key, multiple key groove

Shell Type:

Solid

Connector Locking Method:

Internally threaded coupling ring

Thread Length:

0.280 inches

Operating Temperature Rating:

Between -65.0 degrees celsius and 175.0 degrees celsius

Thread Size:

1.125 inches

Terminal Location:

Back single mating end single contact grouping

Insert Material:

Plastic epoxy single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

Thread Tolerance Class:

6g internal

Thread Series Designator:

Iso m

Specification Data:

81349-mil-c-38999/26 government specification

Specification Or Standard:

81349-d38999/26 specification sheet

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.