NSN 5935-01-564-2781

Electrical Receptacle Connector - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5935-01-564-2781 |
|---|
| Thread Class: |
| 2a and 2a |
| Thread Direction: |
| Right-hand and right-hand |
| Body Style: |
| Straight shape, external coupling |
| Overall Length: |
| 31.5 millimeters |
| Overall Height: |
| 46.0 millimeters |
| Overall Width: |
| 46.0 millimeters |
| Center To Center Distance Between Mounting Facilities Parallel To Height: |
| Between 34.9 millimeters and 38.1 millimeters |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| Between 34.9 millimeters and 38.1 millimeters |
| Distance From Mounting Shoulder To Front Face: |
| 20.1 millimeters |
| Threaded Device Type: |
| Back shell and coupling facility |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 25-35 single mating end |
| Contact Removability: |
| Removable single mating end single contact grouping |
| Polarization Method: |
| Keyway or multiple keyway |
| Insert Position In Deg: |
| 0.0 and 88.0 and 163.0 and 207.0 and 281.0 |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Externally threaded shell |
| Thread Size: |
| 37.0 millimeters and 1.625 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Terminal Type: |
| Crimp single mating end single contact grouping |
| Shell Material: |

Aluminum alloy

NSN 5935-01-564-2781

Electrical Receptacle Connector - Page 2 of 2



| Shell Surface Treatment: |
|---|
| Cadmium |
| Included Contact Quantity: |
| 128 single mating end single contact grouping |
| Included Contact Type: |
| Round pin single mating end single contact grouping |
| Special Features: |
| 1500 cycle pin contact |
| Precious Material And Location: |
| Contacts gold |
| Precious Material: |
| Gold |
| Thread Series Designator: |
| lso s and special acme |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |
| |