

View Online at <https://aerobasegroup.com/nsn/5935-01-564-3002>

**Thread Class:**

2a and 2a

**Thread Direction:**

Right-hand and right-hand

**Body Style:**

Straight shape, external coupling

**Overall Length:**

33.7 millimeters

**Overall Height:**

46.0 millimeters

**Overall Width:**

46.0 millimeters

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

Between 34.9 millimeters and 38.1 millimeters

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 34.9 millimeters and 38.1 millimeters

**Distance From Mounting Shoulder To Front Face:**

20.1 millimeters

**Threaded Device Type:**

Back shell and coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

25-35 single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0 and 67.0 and 164.0 and 218.0 and 280.0

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded shell

**Thread Size:**

37.0 millimeters and 1.625 inches

**Terminal Location:**

Back single mating end single contact grouping

**Terminal Type:**

Crimp single mating end single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium

**Included Contact Quantity:**

128 single mating end single contact grouping

**Included Contact Type:**

Round socket single mating end single contact grouping

**Special Features:**

1500 cycle socket contacts

**Thread Series Designator:**

Iso s and special acme

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-dtl-38999 spec.