NSN 5935-01-564-3166

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-564-3166

Thread Class: 2a and 2a **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 33.7 millimeters **Overall Height:** 26.2 millimeters **Overall Width:** 26.2 millimeters Center To Center Distance Between Mounting Facilities Parallel To Height: Between 18.3 millimeters and 20.6 millimeters Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 20.6 millimeters **Distance From Mounting Shoulder To Front Face:** 20.8 millimeters **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 13089 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 and 124.0 and 152.0 and 219.0 and 265.0 Shell Type: **Connector Locking Method:** Externally threaded shell **Thread Size:** 15.0 millimeters and 0.750 inches **Terminal Location:** Back single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:**

Aluminum alloy

NSN 5935-01-564-3166

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment: Cadmium Included Contact Quantity: 13 single mating end single contact grouping Included Contact Type: Round socket single mating end single contact grouping Special Features: 1500 cycle socket contact Thread Series Designator: Iso s and special acme Shelf Life: N/a Unit Of Measure: --Demilitarization: No

Fiig: A039b0