## NSN 5935-01-565-7522

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-565-7522

Thread Class:  2a and 2b
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape, internal coupling w/strain relief
Body Length:
5.938 inches
Overall Diameter:
1.469 inches
Cable Entrance Diameter:
Between 0.250 inches and 0.437 inches
Threaded Device Type:
Back shell and coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
20-4 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
250.0
250.0 Shell Type:
Shell Type:
Shell Type: Solid
Shell Type: Solid Connector Locking Method:
Shell Type: Solid Connector Locking Method: Internally threaded coupling ring
Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method:
Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp
Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp Thread Size:
Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp Thread Size: 1.188 inches and 1.250 inches Terminal Location:
Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp Thread Size: 1.188 inches and 1.250 inches Terminal Location: Back single mating end single contact grouping
Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp Thread Size: 1.188 inches and 1.250 inches Terminal Location: Back single mating end single contact grouping Terminal Type:
Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp Thread Size: 1.188 inches and 1.250 inches Terminal Location: Back single mating end single contact grouping Terminal Type: Crimp single mating end single contact grouping
Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp Thread Size: 1.188 inches and 1.250 inches Terminal Location: Back single mating end single contact grouping Terminal Type: Crimp single mating end single contact grouping Shell Material:
Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp Thread Size: 1.188 inches and 1.250 inches Terminal Location: Back single mating end single contact grouping Terminal Type: Crimp single mating end single contact grouping Shell Material: Aluminum alloy
Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp Thread Size: 1.188 inches and 1.250 inches Terminal Location: Back single mating end single contact grouping Terminal Type: Crimp single mating end single contact grouping Shell Material: Aluminum alloy Shell Surface Treatment:
Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp Thread Size: 1.188 inches and 1.250 inches Terminal Location: Back single mating end single contact grouping Terminal Type: Crimp single mating end single contact grouping Shell Material: Aluminum alloy Shell Surface Treatment: Cadmium
Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp Thread Size: 1.188 inches and 1.250 inches Terminal Location: Back single mating end single contact grouping Terminal Type: Crimp single mating end single contact grouping Shell Material: Aluminum alloy Shell Surface Treatment:

## NSN 5935-01-565-7522

Electrical Plug Connector - Page 2 of 2



Included Contact Type:
Round pin single mating end single contact grouping
Thread Series Designator:
Unef and unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-dtl-5015 spec.