NSN 5935-01-566-4469

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-566-4469 **Thread Class:** 2a and 2a **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 0.776 inches **Overall Diameter:** 2.140 inches **Distance From Mounting Shoulder To Front Face:** 0.464 inches **Mounting Facility Thickness:** Between 0.062 inches and 0.109 inches **Threaded Device Type:** Back shell and hub **Mating End Quantity: Contact Position Arrangement Style:** 22-21 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 95.0 and 132.0 and 232.0 and 260.0 and 26.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin **Thread Size:** 1.313 inches and 1.750 inches **Terminal Location:** Back single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Cadmium

Included Contact Quantity:

21 single mating end single contact grouping

NSN 5935-01-566-4469

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type:
Round socket single mating end single contact grouping
Thread Series Designator:
Unef and unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig:

A039b0

Mil-std (military Standard):

Mil-dtl-38999 spec.