## NSN 5935-01-569-2567

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-569-2567 **Thread Class:** 2a and 2a **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 37.5 millimeters **Overall Height:** 28.6 millimeters **Overall Width:** 28.6 millimeters Center To Center Distance Between Mounting Facilities Parallel To Height: Between 20.6 millimeters and 23.0 millimeters Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 20.6 millimeters and 23.0 millimeters **Distance From Mounting Shoulder To Front Face:** 19.5 millimeters **Threaded Device Type:** Back shell and hub **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 13-4 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 and 68.0 and 178.0 and 204.0 and 247.0 Shell Type: **Connector Locking Method:** Externally threaded shell **Thread Size:** 18.0 millimeters and 0.875 inches **Terminal Location:** Back single mating end single contact grouping

**Terminal Type:**Crimp single matir

Terminal Type:

Crimp single mating end single contact grouping

**Shell Material:** 

Stainless steel

## NSN 5935-01-569-2567

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Nickel
Included Contact Quantity:
4 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surface gold
Precious Material:
Gold
Thread Series Designator:
lso m and special acme
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0