## NSN 5935-01-569-3865

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-569-3865 **Thread Class:** 2a and 2a **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 37.5 millimeters **Overall Height:** 28.6 millimeters **Overall Width:** 28.6 millimeters Center To Center Distance Between Mounting Facilities Parallel To Height: Between 20.6 millimeters and 23.0 millimeters Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 20.1 millimeters **Distance From Mounting Shoulder To Front Face:** 19.5 millimeters **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 13-4 single mating end **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 and 68.0 and 178.0 and 204.0 and 247.0 Shell Type: Solid **Connector Locking Method:** Externally threaded shell **Thread Size:** 18.0 millimeters and 0.875 inches Back single mating end single contact grouping Crimp single mating end single contact grouping

**Terminal Location: Terminal Type: Shell Material:** Stainless steel **Shell Surface Treatment:** Nickel

## NSN 5935-01-569-3865

Electrical Receptacle Connector - Page 2 of 2



4 single mating end single contact grouping

**Thread Series Designator:** 

Iso m and special acme

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-dtl-38999 spec.