## NSN 5935-01-569-5724

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-569-5724

**Thread Class:** 2a and 2a **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 37.5 millimeters **Overall Height:** 33.3 millimeters **Overall Width:** 33.3 millimeters Center To Center Distance Between Mounting Facilities Parallel To Height: Between 24.6 millimeters and 27.0 millimeters Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 24.7 millimeters and 27.0 millimeters **Distance From Mounting Shoulder To Front Face:** 19.5 millimeters **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 17-6 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 and 116.0 and 160.0 and 191.0 and 311.0 Shell Type: **Connector Locking Method:** Externally threaded shell **Thread Size:** 25.0 millimeters and 1.188 inches **Terminal Location:** Back single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:** 

Onen material

Stainless steel

## NSN 5935-01-569-5724

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Nickel
Included Contact Quantity:
6 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Thread Series Designator:
Iso m and iso m and special acme
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A039b0