## NSN 5935-01-569-9671

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-569-9671 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.280 inches **Overall Diameter:** 2.311 inches **Distance From Mounting Shoulder To Front Face:** 0.890 inches **Mounting Facility Thickness:** 0.104 inches **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** 25-43 single mating end **Contact Removability:** Removable single mating end all contact groupings **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Externally threaded shell **Thread Size:** 44.0 millimeters **Terminal Location:** Back single mating end all contact groupings **Contact Material:** Copper alloy single mating end all contact groupings **Contact Surface Treatment:** Gold single mating end all contact groupings **Insert Material:** Plastic epoxy single mating end **Terminal Type:** 

Crimp single mating end all contact groupings

## NSN 5935-01-569-9671

Electrical Receptacle Connector - Page 2 of 2



| Shell Material:                                      |
|--|
| Aluminum alloy                                       |
| Shell Surface Treatment:                             |
| Nickel   |
| Thread Tolerance Class:                              |
| 6g external  |
| Included Contact Quantity:                           |
| 23 single mating end 1st contact grouping            |
| Included Contact Type:                               |
| Round socket single mating end all contact groupings |
| Precious Material And Location:                      |
| Contact surfaces gold                                |
| Precious Material:                                   |
| Gold   |
| Thread Series Designator:                            |
| Iso m  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:                                     |
|  |
| Demilitarization:                                    |
| No   |
| Fiig:  |
| A039b0   |
| Mil-std (military Standard):                         |
| Mil-dtl-38999 spec.                                  |