Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-569-9671

| Thread Class: |
|--|
| 2a |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Straight shape, external coupling |
| Overall Length: |
| 1.280 inches |
| Overall Diameter: |
| 2.311 inches |
| Distance From Mounting Shoulder To Front Face: |
| 0.890 inches |
| Mounting Facility Thickness: |
| 0.104 inches |
| Threaded Device Type: |
| Back shell |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 25-43 single mating end |
| Contact Removability: |
| Removable single mating end all contact groupings |
| Polarization Method: |
| Keyway or multiple keyway |
| Insert Position In Deg: |
| 0.0 |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Externally threaded shell |
| Thread Size: |
| 44.0 millimeters |
| Terminal Location: |
| Back single mating end all contact groupings |
| Contact Material: |
| Copper alloy single mating end all contact groupings |
| Contact Surface Treatment: |
| Gold single mating end all contact groupings |
| Insert Material: |
| Plastic epoxy single mating end |
| Terminal Type: |
| Crimp single mating end all contact groupings |



| Shell Material: |
|--|
| Aluminum alloy |
| Shell Surface Treatment: |
| Nickel |
| Thread Tolerance Class: |
| 6g external |
| Included Contact Quantity: |
| 23 single mating end 1st contact grouping |
| Included Contact Type: |
| Round socket single mating end all contact groupings |
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material: |
| Gold |
| Thread Series Designator: |
| lso m |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |
| Mil-std (military Standard): |
| Mil-dtl-38999 spec. |
| |
| |