## NSN 5935-01-570-7025

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-570-7025 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 0.560 inches **Overall Height:** 1.812 inches **Overall Width:** 1.812 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.750 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.750 inches **Distance From Mounting Shoulder To Front Face:** 0.790 inches **Threaded Device Type:** Back shell **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 25-35 all mating ends **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 15.0 and 105.0 and 132.0 and 220.0 and 265.0 Shell Type: **Connector Locking Method:** Bayonet pin **Thread Size:** 1.438 inches **Terminal Location:** Back single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping

Shell Material: Aluminum alloy

## NSN 5935-01-570-7025

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Nickel
Included Contact Quantity:
128 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material:
Gold
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-dtl-38999 spec.