NSN 5935-01-571-2339

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-571-2339 **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 33.6 millimeters **Overall Height:** 36.5 millimeters **Overall Width:** 36.5 millimeters Center To Center Distance Between Mounting Facilities Parallel To Height: 27.0 millimeters Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 27.0 millimeters **Distance From Mounting Shoulder To Front Face:** 19.5 millimeters **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 19-35 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 and 50.0 and 160.0 and 190.0 and 225.0 Shell Type: Solid **Connector Locking Method:** Externally threaded shell **Thread Size:** 34.0 millimeters and 1.250 inches **Terminal Location:** Back single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping

Shell Material:

Stainless steel

NSN 5935-01-571-2339

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Passivate
Thread Tolerance Class:
2a external
Included Contact Quantity:
66 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material:
Gold
Thread Series Designator:
Iso s and special acme
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:

A039b0