Electrical Plug Connector - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5935-01-571-3005

2b Thread Direction: Righ-hand Body Style: Angle shape wicable clamp Overall Diameter: 2.469 inches Body Style: 2.469 inches Body Style: Contact Daimeter: 0.875 inches Mating End Quantity: 1 Contact Position Arrangement Style: 36-5 single mating end Polarization Method: Keyway or multiple keyway Insert Position In Deg: 12.0 Connector Locking Method: Insert Position In Deg: 12.0.0 Connector Cable Strain Relief Method: Cable Capping Length: 1.250 inches Distance From Centerline To Connector End: 3.500 inches Distance From Centerline To Cable End: 4.625 inches Thread Size: 2.500 inches Distance From Centerline To Cable End: 4.625 inches Thread Size: 2.500 inches Terminal Location: Back single mating end single contact grouping	Thread Class:
Right-hand Body Style: Angle shape w/cable clamp Overall Diameter: 2.469 inches Body Angle In Deg: 135.0 Cable Entrance Diameter: 0.875 inches Mating End Quantity: 1 Contact Position Arrangement Style: 36-5 single mating end Polarization Method: Keyway or multiple keyway Insert Position In Deg: 120.0 Connector Locking Method: Insert Position In Deg: 120.0 Connector Locking Method: Insert Position In Deg: 120.0 Connector Locking Method: Internally threaded coupling ring Cable Capening Length: 1.250 inches Distance From Conterline To Connector End: 3.500 inches Distance From Conterline To Cable End: 4.625 inches Thready Qty Per Inch (tpi): 16 Threads Size 2.250 inches Terminal Location: Back single mating end single contact grouping Threinal Type: </th <th></th>	
Right-hand Body Style: Angle shape w/cable clamp Overall Diameter: 2.469 inches Body Angle In Deg: 135.0 Cable Entrance Diameter: 0.875 inches Mating End Quantity: 1 Contact Position Arrangement Style: 36-5 single mating end Polarization Method: Keyway or multiple keyway Insert Position In Deg: 120.0 Connector Locking Method: Insert Position In Deg: 120.0 Connector Locking Method: Insert Position In Deg: 120.0 Connector Locking Method: Internally threaded coupling ring Cable Capening Length: 1.250 inches Distance From Conterline To Connector End: 3.500 inches Distance From Conterline To Cable End: 4.625 inches Thready Qty Per Inch (tpi): 16 Threads Size 2.250 inches Terminal Location: Back single mating end single contact grouping Threinal Type: </th <th>Thread Direction:</th>	Thread Direction:
Body Style: Angle shape wicable clamp Overall Diameter: 2.469 inches Body Angle In Deg: 135.0 Cable Entrance Diameter: 0.875 inches Mating End Quantity: 1 Contact Position Arrangement Style: 36-5 single mating end Polarization Method: Reyway or multiple keyway Insert Position In Deg: 120.0 Connector Locking Method: Interrally threaded coupling ring Connector Locking Method: Interrally threaded coupling ring Cable Clamp Cable Opening Length: 1.250 inches Distance From Centerline To Connector End: 3.500 inches Distance From Centerline To Cable End: 4.625 inches Thready Gty Per Inch (tpi): 16 Thread Size: 2.250 inches Terminal Location: Back single mating end single contact grouping Shell Material: Aurnium alloy	
Angle shape w/cable clamp Overall Diameter: 2:489 inches Body Angle In Deg: 135:0 Cable Entrance Diameter: 0:875 inches Mating End Quantity: 1 Contact Position Arrangement Style: 36-5 single mating end Polarization Method: Keyway or multiple keyway Insert Position In Deg: 12:0.0 Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable Chaping Length: 1:250 inches Distance From Centerline To Connector End: 3:500 inches Distance From Centerline To Cable End: 4:625 inches Trencidy Cay Per Inch (tpi): 16 Tremial Location: 2:250 inches Terminal Location: Cack single mating end single contact grouping Shell Material: Aurnium alley	-
Overall Diameter:2.469 inchesBody Angle In Deg:135.0Cable Entrance Diameter:0.875 inchesMating End Quantity:1Contact Position Arrangement Style:36-5 single mating endPolarization Method:Keyway or multiple keywayInsert Position In Deg:10.0Connector Locking Method:Internally threaded coupling ringConnector Cable Strain Relief Method:Cable clampCable clampCablesDistance From Centerline To Connector End:3:500 inchesDistance From Centerline To Cable End:4:625 inchesChreed Size:2:520 inchesChreed Size:2:520 inchesChreed Size:2:520 inchesFirminal Location:Cable single mating end single contact groupingChreed Size:Cimp single mating end single contact groupingShell Materiai:Aurninu alloyIncluded Contact Quanting:	
2.489 inches Body Angle In Deg: 135.0 Cable Entrance Diameter: 0.875 inches Mating End Quantity: 1 Contact Position Arrangement Style: 36-5 single mating end Polarization Method: Keyway or multiple keyway Insert Position In Deg: 12.0 Contact Coking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable Camp Cable Copening Length: 1.250 inches Distance From Centerline To Connector End: 3.500 inches Distance From Centerline To Cable End: 4.625 inches Thready Gty Per Inch (tpi): 16 Tread Size: 2.500 inches Terminal Location: 2.500 inches Thready Gty Per Inch (tpi): 16 Terminal Location: Back single mating end single contact grouping Terminal Location: Back single mating end single contact grouping Ching single mating end single contact grouping Shell Ma	
Body Angle In Deg: 135.0 Cable Entrance Diameter: 0.875 inches Mating End Quantity: 1 Contact Position Arrangement Style: 38-5 single mating end Polarization Method: Keyway or multiple keyway Insert Position In Deg: 12.0 Connector Locking Method: Internally threaded coupling ring Connector Coble Strain Relief Method: Cable Clamp Cable Clamp Distance From Centerline To Connector End: 3.500 inches Distance From Centerline To Cable End: 4.625 inches Thready Qay Per Inch (tpi): 16 Thread Size: 2.500 inches Thread Size: 2.500 inches Thread Size: 2.520 inches Thread Size: 2.520 inches Terminal Location: Back single mating end single contact grouping Terminal Location: Chape single mating end single contact grouping Shell Materiat: Auruinum alloy	
135.0 Cable Entrance Diameter: 0.875 inches Mating End Quantity: 1 Contact Position Arrangement Style: 36-5 single mating end Polarization Method: Keyway or multiple keyway Insert Position In Deg: 120.0 Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp Cable Opening Length: 1.250 inches Distance From Centerline To Connector End: 3.500 inches Distance From Centerline To Cable End: 4.625 inches Thready Quy Per Inch (tpi): 1.6 Thread Size: 2.250 inches Terminal Location: Back single mating end single contact grouping Terminal Type: Crimp single mating end single contact grouping Shell Material: Auminum alloy Houted Contact Quantity:	
Cable Entrance Diameter: 0.875 inches Mating End Quantity: 1 Contact Position Arrangement Style: 38-5 single mating end Polarization Method: Keyway or multiple keyway Insert Position In Deg: 120.0 Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp Distance From Centerline To Connector End: 3.500 inches Distance From Centerline To Cable End: 4.625 inches Thready Qty Per Inch (tpi): 16 Thread Size: 2.250 inches Distance From Centerline To cable End: 4.625 inches Thread Size: 2.250 inches Distance From Centerline To Cable End: 4.625 inches Thread Size: 2.250 inches Distance From Centerline To Cable End: 2.500 inches Distance From Centerline To Cable End: 2.625 inches Thread Size: 2.520 inches Distance From Centerline To cable	
0.875 inches Mating End Quantity: 1 Contact Position Arrangement Style: 36-5 single mating end Polarization Method: Keyway or multiple keyway Insert Position In Deg: 120.0 Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable Opening Length: 1.250 inches Distance From Centerline To Connector End: 3.500 inches Distance From Centerline To Cable End: 4.625 inches Thready Qty Per Inch (tpi): 16 Thread Size: 2.250 inches Cating Immit In Guanting Immit Immi	
Mating End Quantity: 1 Contact Position Arrangement Style: 36-5 single mating end Polarization Method: Keyway or multiple keyway Insert Position In Deg: 120.0 Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable Camp Cable Copening Length: 1.250 inches Distance From Centerline To Connector End: 3.500 inches Distance From Centerline To Cable End: 4.625 inches Thready Qty Per Inch (tpi): 16 Thread Size: 2.250 inches Catingle mating end single contact grouping Terminal Location: Back single mating end single contact grouping Chirp single mating end single contact grouping Shell Material: Atuminum alloy Houlded Contact Quantity:	
1 Contact Position Arrangement Style: 36-5 single mating end Polarization Method: Keyway or multiple keyway Insert Position In Deg: 120.0 Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable champ Cable Opening Length: 1.250 inches Distance From Centerline To Connector End: 3.500 inches Distance From Centerline To Cable End: 4.625 inches Thready Qty Per Inch (tpi): 16 Thread Size: 2.250 inches Erminal Location: Back single mating end single contact grouping Terminal Location: Back single mating end single contact grouping Shell Material: Aluminum alloy Included Contact Quantity:	
Contact Position Arrangement Style: 36-5 single mating end Polarization Method: Keyway or multiple keyway Insert Position In Deg: 120.0 Connector Locking Method: Internality threaded coupling ring Connector Cable Strain Relief Method: Cable clamp Cable Opening Length: 1.250 inches Distance From Centerline To Connector End: 3.500 inches Distance From Centerline To Cable End: 4.625 inches Thready Qty Per Inch (tpi): 16 Thread Size: 2.250 inches Erminal Location: Back single mating end single contact grouping Terminal Location: Ching Single mating end single contact grouping Shell Material: Aluminum alloy	
36-5 single mating end Polarization Method: Keyway or multiple keyway Insert Position In Deg: 120.0 Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp Cable Comp Distance From Centerline To Connector End: 3.500 inches Distance From Centerline To Cable End: 4.625 inches Thready Qty Per Inch (tpi): 16 Thread Size: 2.250 inches Eack single mating end single contact grouping Terminal Location: Back single mating end single contact grouping Crimp single mating end single contact grouping Shell Materiai: Aluminum alloy Included Contact Quantity:	
Polarization Method: Keyway or multiple keyway Insert Position In Deg: 120.0 Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp Cable Opening Length: 1.250 inches Distance From Centerline To Connector End: 3.500 inches Distance From Centerline To Cable End: 4.625 inches Thready Qty Per Inch (tpi): 16 Thread Size: 2.250 inches Farminal Location: Back single mating end single contact grouping Terminal Type: Crimp single mating end single contact grouping Shell Materiai: Aluminum alloy	
Keyway or multiple keyway Insert Position In Deg: 120.0 Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp Cable Opening Length: 1.250 inches Distance From Centerline To Connector End: 3.500 inches Distance From Centerline To Cable End: 4.625 inches Thready Qty Per Inch (tpi): 16 Thread Size: 2.550 inches Forminal Location: Back single mating end single contact grouping Farminal Type: Crimp single mating end single contact grouping Aluminum alloy Huminum alloy	
Issert Position In Deg: 120.0 Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp Cable Opening Length: 1.250 inches Distance From Centerline To Connector End: 3.500 inches Distance From Centerline To Cable End: 4.625 inches Thready Qty Per Inch (tpi): 16 Thread Size: 2.520 inches Thread Size: 2.520 inches Thread Size: 2.520 inches Chrimal Location: Back single mating end single contact grouping Farminal Location: Crimp single mating end single contact grouping Aluminum alloy Huminum alloy	
120.0 Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp Cable Opening Length: 1.250 inches Distance From Centerline To Connector End: 3.500 inches Distance From Centerline To Cable End: 4.625 inches Thready Qty Per Inch (tpi): 16 Thread Size: 2.250 inches Ferminal Location: Back single mating end single contact grouping Terminal Type: Crimp single mating end single contact grouping Shell Material: Aluminum alloy Included Contact Quantity:	
Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp Cable Opening Length: 1.250 inches Distance From Centerline To Connector End: 3.500 inches Distance From Centerline To Cable End: 4.625 inches Thready Qty Per Inch (tpi): 16 Thread Size: 2.250 inches Terminal Location: Back single mating end single contact grouping Cerminal Type: Crimp single mating end single contact grouping Shell Material: Aluminum alloy	
Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp Cable Opening Length: 1.250 inches Distance From Centerline To Connector End: 3.500 inches Distance From Centerline To Cable End: 4.625 inches Thready Qty Per Inch (tpi): 16 Thread Size: 2.250 inches Terminal Location: Back single mating end single contact grouping Cerminal Type: Crimp single mating end single contact grouping Shell Material: Aluminum alloy	Connector Locking Method:
Cable clampCable Opening Length:1.250 inchesDistance From Centerline To Connector End:3.500 inchesDistance From Centerline To Cable End:4.625 inchesThready Qty Per Inch (tpi):16Thread Size:2.250 inchesTerminal Location:Back single mating end single contact groupingTerminal Type:Crimp single mating end single contact groupingShell Material:Aluminum alloyIncluded Contact Quantity:	
Cable Opening Length:1.250 inchesDistance From Centerline To Connector End:3.500 inchesDistance From Centerline To Cable End:4.625 inchesThready Qty Per Inch (tpi):16Thread Size:2.250 inchesTerminal Location:Back single mating end single contact groupingTerminal Type:Crimp single mating end single contact groupingShell Material:Aluminum alloyIncluded Contact Quantity:	Connector Cable Strain Relief Method:
 1.250 inches Distance From Centerline To Connector End: 3.500 inches Distance From Centerline To Cable End: 4.625 inches Thready Qty Per Inch (tpi): 16 Thread Size: 2.250 inches Terminal Location: Back single mating end single contact grouping Terminal Type: Crimp single mating end single contact grouping Shell Material: Aluminum alloy Included Contact Quantity: 	Cable clamp
Distance From Centerline To Connector End:3.500 inchesDistance From Centerline To Cable End:4.625 inchesThready Qty Per Inch (tpi):16Thread Size:2.250 inchesTerminal Location:Back single mating end single contact groupingTerminal Type:Crimp single mating end single contact groupingShell Material:Aluminum alloyIncluded Contact Quantity:	Cable Opening Length:
3.500 inchesDistance From Centerline To Cable End:4.625 inchesThready Qty Per Inch (tpi):16Thread Size:2.250 inchesTerminal Location:Back single mating end single contact groupingTerminal Type:Crimp single mating end single contact groupingShell Material:Aluminum alloyIncluded Contact Quantity:	1.250 inches
Distance From Centerline To Cable End:4.625 inchesThready Qty Per Inch (tpi):1616Thread Size:2.250 inchesTerminal Location:Back single mating end single contact groupingTerminal Type:Crimp single mating end single contact groupingShell Material:Aluminum alloyIncluded Contact Quantity:	Distance From Centerline To Connector End:
4.625 inches Thready Qty Per Inch (tpi): 16 Thread Size: 2.250 inches Terminal Location: Back single mating end single contact grouping Terminal Type: Crimp single mating end single contact grouping Shell Material: Aluminum alloy	3.500 inches
Thready Qty Per Inch (tpi):16Thread Size:2.250 inchesTerminal Location:Back single mating end single contact groupingTerminal Type:Crimp single mating end single contact groupingShell Material:Aluminum alloyIncluded Contact Quantity:	Distance From Centerline To Cable End:
 16 Thread Size: 2.250 inches Terminal Location: Back single mating end single contact grouping Terminal Type: Crimp single mating end single contact grouping Shell Material: Aluminum alloy Included Contact Quantity: 	4.625 inches
Thread Size:2.250 inchesTerminal Location:Back single mating end single contact groupingTerminal Type:Crimp single mating end single contact groupingShell Material:Aluminum alloyIncluded Contact Quantity:	Thready Qty Per Inch (tpi):
2.250 inches Terminal Location: Back single mating end single contact grouping Terminal Type: Crimp single mating end single contact grouping Shell Material: Aluminum alloy Included Contact Quantity:	16
Terminal Location: Back single mating end single contact grouping Terminal Type: Crimp single mating end single contact grouping Shell Material: Aluminum alloy Included Contact Quantity:	Thread Size:
Back single mating end single contact grouping Terminal Type: Crimp single mating end single contact grouping Shell Material: Aluminum alloy Included Contact Quantity:	2.250 inches
Terminal Type: Crimp single mating end single contact grouping Shell Material: Aluminum alloy Included Contact Quantity:	Terminal Location:
Crimp single mating end single contact grouping Shell Material: Aluminum alloy Included Contact Quantity:	Back single mating end single contact grouping
Shell Material: Aluminum alloy Included Contact Quantity:	Terminal Type:
Aluminum alloy Included Contact Quantity:	Crimp single mating end single contact grouping
Included Contact Quantity:	Shell Material:
	Aluminum alloy
4 single mating end single contact grouping	Included Contact Quantity:
	4 single mating end single contact grouping

Electrical Plug Connector - Page 2 of 2



Included Contact Type:

Round pin single mating end single contact grouping

Thread Series Designator:

Un

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A039b0