

View Online at <https://aerobasegroup.com/nsn/5935-01-571-6382>

Thread Class:

2a and 2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

2.030 inches

Overall Diameter:

Between 0.850 inches and 0.900 inches

Environmental Protection:

Moisture proof and vibration proof and salt water resistant

Cable Entrance Diameter:

Between 0.492 inches and 0.495 inches

Distance From Mounting Shoulder To Front Face:

Between 0.912 inches and 0.940 inches

Mounting Facility Thickness:

0.250 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

N single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Frequency Rating:

11000.0 megahertz single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Connector Cable Strain Relief Method:

Compression nut

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Thread Size:

0.625 inches and 0.625 inches

Terminal Location:

Back single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Included Contact Quantity:

1 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round w/double flat

Included Contact Type:

Coaxial socket single mating end single contact grouping

Test Data Document:

81349-mil-c-39012 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef and unef

Specification Data:

81349-mil-c-39012/3 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0