

View Online at <https://aerobasegroup.com/nsn/5935-01-574-0358>

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

31.5 millimeters

Overall Height:

36.5 millimeters

Overall Width:

36.5 millimeters

Unthreaded Mounting Hole Diameter:

Between 3.2 millimeters and 3.3 millimeters

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 26.9 millimeters and 29.4 millimeters

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 26.9 millimeters and 29.4 millimeters

Distance From Mounting Shoulder To Front Face:

2.5 millimeters

Threaded Device Type:

Back shell and coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

19-32 single mating end

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

65.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

End Application:

Aircraft, hercules c-130

Thread Size:

28.0 millimeters and 1.375 inches

Thread Pitch In Millimeters:

1.0

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Nickel

Shell Surface Treatment Specification:

Mil-c-26074 military specification single treatment response

Thread Tolerance Class:

6g external

Included Contact Quantity:

32 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material:

Gold

Thread Series Designator:

Iso m

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A039b0

Mil-std (military Standard):

Mil-c-26074 spec.