NSN 5935-01-575-1688

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-575-1688 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.025 inches **Overall Height:** 1.043 inches **Overall Width:** 1.043 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 0.719 inches and 0.812 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 0.719 inches and 0.812 inches **Distance From Mounting Shoulder To Front Face:** Between 0.815 inches and 0.820 inches **Mating End Quantity: Contact Position Arrangement Style:** 36100 single mating end **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 95.0 and 141.0 and 208.0 and 236.0 **Connector Locking Method:** Externally threaded shell **Features Provided:** Color band engagement indicator **Thread Size:** 0.750 inches **Terminal Location:** Back single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:** Aluminum **Shell Surface Treatment:** Cadmium

oud.mam.

Included Contact Quantity:

6 single mating end single contact grouping

NSN 5935-01-575-1688

Electrical Receptacle Connector - Page 2 of 2



Included	Contact	Ty	pe:
----------	---------	----	-----

Round socket single mating end single contact grouping

Special Features:

The shell finish is 500 hour salt spray resistant.

Color:

Olive drab

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0