

View Online at <https://aerobasegroup.com/nsn/5935-01-581-2439>

**Body Style:**

Straight shape

**Environmental Protection:**

Dustproof

**Contact Maximum Current Rating In Amps:**

15.0 all mating ends all contact groupings

**Contact Maximum Ac Voltage Rating In Volts:**

125.0 all mating ends all contact groupings

**Connector Locking Method:**

Screw

**End Application:**

LAVC-2A-2;2-3550

**Terminal Type:**

Screw single mating end 1st contact grouping

**Shell Material:**

Plastic polytetrafluoroethylene

**Product Name:**

Elastogrip series connector body-yellow

**Special Features:**

Straight; nema 5-15r; 2 pole, 3 wire grounding; elastogrip; yellow; cord ia 0.300-0.655inches; straight blade connector; suitability ip20; housing pvc; retainer polycarbonate-clear; cord clamp material nylon-yellow; terminal screw no.8-32 brass, multiple drive; ground screw-no.8-32 brass multiple drive-green; contact holder nylon-natural; power contacts 0.40inch copper alloy; dielectric voltage 2000v min; terminal accommodation no.14-10 awg

**Special Test Features:**

Ul498 file e1706, csa cert to c22.2 no.42 file 280; ul94hnb or better

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0