

View Online at <https://aerobasegroup.com/nsn/5935-01-581-2439>

Body Style:

Straight shape

Environmental Protection:

Dustproof

Contact Maximum Current Rating In Amps:

15.0 all mating ends all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

125.0 all mating ends all contact groupings

Connector Locking Method:

Screw

End Application:

LAVC-2A-2;2-3550

Terminal Type:

Screw single mating end 1st contact grouping

Shell Material:

Plastic polytetrafluoroethylene

Product Name:

Elastogrip series connector body-yellow

Special Features:

Straight; nema 5-15r; 2 pole, 3 wire grounding; elastogrip; yellow; cord ia 0.300-0.655inches; straight blade connector; suitability ip20; housing pvc; retainer polycarbonate-clear; cord clamp material nylon-yellow; terminal screw no.8-32 brass, multiple drive; ground screw-no.8-32 brass multiple drive-green; contact holder nylon-natural; power contacts 0.40inch copper alloy; dielectric voltage 2000v min; terminal accommodation no.14-10 awg

Special Test Features:

Ul498 file e1706, csa cert to c22.2 no.42 file 280; ul94hnb or better

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0