## NSN 5935-01-582-1796

Thread Class: 2a and 2b

**Thread Direction:** 

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-582-1796

Right-hand and right-hand **Body Style:** Angle shape w/cable clamp **Overall Diameter:** 1.312 inches **Body Angle In Deg:** 135.0 **Cable Entrance Diameter:** Between 0.344 inches and 0.562 inches **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 40489 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Key or multiple key Shell Type: Solid **Connector Locking Method:** Internally threaded coupling ring **Connector Cable Strain Relief Method:** Cable clamp **Distance From Centerline To Connector End: 7.727** inches **Distance From Centerline To Cable End:** 5.557 inches Thready Qty Per Inch (tpi): 20 **Thread Size:** 0.750 inches and 0.750 inches **Terminal Location:** Back single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:** Aluminum alloy

## NSN 5935-01-582-1796

Electrical Plug Connector - Page 2 of 2



Shell Surface Treatment:
Cadmium
Included Contact Quantity:
7 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material:
Gold
Thread Series Designator:
Unef and double stub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A039b0