## NSN 5935-01-584-3110

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-584-3110 **Thread Class:** 2a and 2a **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 20.1 millimeters **Overall Height:** 46.0 millimeters **Overall Width:** 46.0 millimeters Center To Center Distance Between Mounting Facilities Parallel To Height: Between 34.9 millimeters and 38.1 millimeters Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 34.9 millimeters and 38.1 millimeters **Distance From Mounting Shoulder To Front Face:** 33.7 millimeters **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 25-24 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 and 50.0 and 160.0 and 190.0 and 225.0 Shell Type: **Connector Locking Method:** Externally threaded shell **Thread Size:** 37.0 millimeters and 1.625 inches **Terminal Location:** Back single mating end single contact grouping **Terminal Type:** 

**Shell Material:** Plastic

Crimp single mating end single contact grouping

## NSN 5935-01-584-3110

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Cadmium
Thread Tolerance Class:
6h external
Included Contact Quantity:
24 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surface gold
Precious Material:
Gold
Thread Series Designator:
lso s and special acme
Shelf Life:
N/a
Unit Of Measure:
<del>.</del>
Demilitarization:
No
Fiig:
A039b0