NSN 5935-01-585-0055

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-585-0055 **Thread Class:** 2a and 2a **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 2.125 inches **Overall Diameter:** 1.812 inches **Distance From Mounting Shoulder To Front Face:** 0.970 inches **Mounting Facility Thickness:** 0.128 inches **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 18-4 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Key or multiple key **Insert Position In Deg:** 80.0 Shell Type: Solid **Connector Locking Method:** Externally threaded shell Thready Qty Per Inch (tpi): 18 and 18 **Thread Size:** 1.063 inches and 1.125 inches **Terminal Location:** Back single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:** Aluminum **Shell Surface Treatment:**

Cadmium

NSN 5935-01-585-0055

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity: 4 single mating end single contact grouping Included Contact Type: Round socket single mating end single contact grouping Precious Material: Gold Thread Series Designator: Unef and unef

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-dtl-5015 spec.