NSN 5935-01-585-0074

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-585-0074 **Thread Class:** 2a and 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 2.125 inches **Overall Diameter:** 1.937 inches **Unthreaded Mounting Hole Diameter:** 1.255 inches **Distance From Mounting Shoulder To Front Face:** 0.970 inches **Mounting Facility Thickness:** 0.128 inches **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 7 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Key or multiple key **Insert Position In Deg:** 250.0 Shell Type: Solid **Connector Locking Method:** Externally threaded shell Thready Qty Per Inch (tpi): 18 and 18 **Thread Size:** 1.188 inches and 1.250 inches **Terminal Location:** Back single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping

Shell Material:

Aluminum

NSN 5935-01-585-0074

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Cadmium
Included Contact Quantity:
7 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material:
Gold
Thread Series Designator:
Unef and unef
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):

Mil-dtl-5015 spec.