Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-587-2482

## Thread Class:

2a and 2a

## **Thread Direction:**

Right-hand and right-hand

## Body Style:

Straight shape, external coupling

#### **Overall Length:**

2.062 inches

#### **Overall Height:**

1.278 inches

#### **Overall Width:**

### 1.278 inches

### Center To Center Distance Between Mounting Facilities Parallel To Height:

#### 0.968 inches

### Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.968 inches

# Distance From Mounting Shoulder To Front Face:

0.898 inches

### **Threaded Device Type:**

Back shell and coupling facility

### Mating End Quantity:

1

## **Contact Position Arrangement Style:**

15-21 single mating end

### **Contact Removability:**

Removable single mating end single contact grouping

### **Polarization Method:**

Keyway or multiple keyway

### **Insert Position In Deg:**

0.0 and 67.0 and 164.0 and 236.0 and 280.0

### Shell Type:

Solid

## **Connector Locking Method:**

Externally threaded shell

# Thready Qty Per Inch (tpi):

20

### Thread Size:

1.000 inches and 1.062 inches

## **Terminal Location:**

Back single mating end single contact grouping

### **Terminal Type:**

Crimp single mating end single contact grouping

Electrical Receptacle Connector - Page 2 of 2



**Shell Material:** Stainless steel **Shell Surface Treatment:** Cadmium **Included Contact Quantity:** 21 single mating end single contact grouping Included Contact Type: Round socket single mating end single contact grouping **Precious Material:** Gold **Thread Series Designator:** Unef and double stub Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A039b0 Mil-std (military Standard): Mil-dtl-28840 spec.