## NSN 5935-01-588-5626



Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-01-588-5626 **Thread Class:** 2a and 2a **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 2.125 inches **Overall Height:** 2.500 inches **Overall Width:** 2.500 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.875 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.938 inches **Distance From Mounting Shoulder To Front Face:** 1.938 inches **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 36-52 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Key or multiple key **Insert Position In Deg:** 0.0 Shell Type: **Connector Locking Method:** Externally threaded shell Thready Qty Per Inch (tpi): 16 and 16 **Thread Size:** 2.250 inches and 2.250 inches

**Terminal Location:** 

Back single mating end single contact grouping

**Terminal Type:** 

Crimp single mating end single contact grouping

## NSN 5935-01-588-5626

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Aluminum alloy
Shell Surface Treatment:
Nickel
Included Contact Quantity:
52 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material:
Gold
Thread Series Designator:
Un and un
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-c-5015 spec.