## NSN 5935-01-588-6011

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-588-6011

View Online at https://aerobasegroup.com/nsn/5935-01-588-6011
Thread Class:
2a
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape, external coupling
Overall Length:
33.7 millimeters
Overall Height:
42.9 millimeters
Overall Width:
42.9 millimeters
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 31.7 millimeters and 34.9 millimeters
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 31.7 millimeters and 34.9 millimeters
Distance From Mounting Shoulder To Front Face:
20.1 millimeters
Threaded Device Type:
Back shell and coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
23-55 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0 and 67.0 and 164.0 and 218.0 and 280.0
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Thread Size:
34.0 millimeters and 1.500 inches
Terminal Location:
Back single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:

Plastic

## NSN 5935-01-588-6011

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Cadmium
Thread Tolerance Class:
6g external
Included Contact Quantity:
55 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material:
Gold
Thread Series Designator:
lso s and special acme
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0