

View Online at <https://aerobasegroup.com/nsn/5935-01-589-7726>

Body Style:

Straight shape, internal coupling

Overall Diameter:

0.437 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

Bn single mating end

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end all contact groupings

Connector Locking Method:

Internally threaded coupling ring

Connector Cable Strain Relief Method:

Crimp type

Radio Frequency Type Contact Characteristic Impedance In Ohms:

11.0 single mating end all contact groupings

Contact Material:

Beryllium single mating end all contact groupings and copper single mating end all contact groupings and zinc single mating end all contact groupings

Contact Surface Treatment:

Silver single mating end all contact groupings or gold single mating end all contact groupings

Insert Material:

Copper single mating end and zinc single mating end

Shell Material:

Copper and zinc

Shell Surface Treatment:

Nickel

Included Contact Quantity:

1 single mating end all contact groupings

Included Contact Type:

Coaxial socket single mating end all contact groupings

Product Name:

Straight crimp plug - standard cable

Special Features:

Shock, vibration, moisture, corrosion, temp cycling, and altitude resistant; 7/16 inch threaded coupling

Precious Material And Location:

Male and female center contacts gold and male and female center contacts silver

Precious Material:

Gold or silver

Specification Data:

96906-mil-std-202 methods 101b, 102d, 105c, 106, 202, 204d government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0