

View Online at <https://aerobasegroup.com/nsn/5935-01-589-7726>

**Body Style:**

Straight shape, internal coupling

**Overall Diameter:**

0.437 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

Bn single mating end

**Contact Maximum Ac Voltage Rating In Volts:**

500.0 single mating end all contact groupings

**Connector Locking Method:**

Internally threaded coupling ring

**Connector Cable Strain Relief Method:**

Crimp type

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

11.0 single mating end all contact groupings

**Contact Material:**

Beryllium single mating end all contact groupings and copper single mating end all contact groupings and zinc single mating end all contact groupings

**Contact Surface Treatment:**

Silver single mating end all contact groupings or gold single mating end all contact groupings

**Insert Material:**

Copper single mating end and zinc single mating end

**Shell Material:**

Copper and zinc

**Shell Surface Treatment:**

Nickel

**Included Contact Quantity:**

1 single mating end all contact groupings

**Included Contact Type:**

Coaxial socket single mating end all contact groupings

**Product Name:**

Straight crimp plug - standard cable

**Special Features:**

Shock, vibration, moisture, corrosion, temp cycling, and allitude resistant; 7/16 inch threaded coupling

**Precious Material And Location:**

Male and female center contacts gold and male and female center contacts silver

**Precious Material:**

Gold or silver

**Specification Data:**

96906-mil-std-202 methods 101b, 102d, 105c, 106, 202, 204d government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0