NSN 5935-01-593-9372

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-593-9372 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.662 inches **Overall Height:** Between 1.157 inches and 1.219 inches **Overall Width:** Between 1.157 inches and 1.219 inches **Unthreaded Mounting Hole Diameter:** Between 0.115 inches and 0.130 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.906 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.906 inches **Distance From Mounting Shoulder To Front Face:** Between 0.562 inches and 0.593 inches **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** 14s-7 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Key, multiple key groove **Insert Position In Deg: Connector Locking Method:** Externally threaded shell **End Application:** Nuclear power plants **Thread Size:** 0.875 inches **Terminal Location:**

Back single mating end single contact grouping **Terminal Type:**

Crimp single mating end single contact grouping

NSN 5935-01-593-9372

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Aluminum alloy
Included Contact Quantity:
3 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Special Features:
The shell is 500 hour salt spray resistant.
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A039b0