

View Online at <https://aerobasegroup.com/nsn/5935-01-600-8388>

**Thread Class:**

2b

**Thread Direction:**

Right-hand and right-hand

**Body Style:**

Straight shape, internal coupling

**Overall Length:**

33.2 millimeters

**Overall Diameter:**

48.0 millimeters

**Environmental Protection:**

Corrosion resistant and fungus resistant and moisture resistant and salt spray proof and shock resistant and vibration resistant and weather resistant

**Threaded Device Type:**

Back shell and coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

25-43 single mating end

**Contact Removability:**

Removable single mating end all contact groupings

**Polarization Method:**

Key or multiple key

**Insert Position In Deg:**

0.0 and 66.0 and 140.0 and 200.0 and 257.0

**Shell Type:**

Solid

**Connector Locking Method:**

Internally threaded coupling ring

**End Application:**

V-22 osprey

**Operating Temperature Rating:**

Between -65.0 degrees celsius and 175.0 degrees celsius

**Thread Size:**

37.0 millimeters and 1.625 inches

**Terminal Location:**

Back single mating end all contact groupings

**Terminal Type:**

Crimp single mating end all contact groupings

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium

**Thread Tolerance Class:**

6g external

**Included Contact Quantity:**

23 single mating end 2nd contact grouping

**Included Contact Type:**

Round pin single mating end all contact groupings

**Product Name:**

Connector, plug, special anti-decoupling, d38999 iii type

**Special Features:**

Contacts per m39029/58-363 and /58-363. Connector meets the requirements of mil-dtl-38999 plus additional vibration requirements to ensure anti decoupling and metal to metal bottoming

**Color:**

Olive drab

**Precious Material And Location:**

Contact surfaces gold

**Precious Material:**

Gold

**Thread Series Designator:**

Iso m and special acme

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0