## NSN 5935-01-603-7316

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-603-7316
Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
1.625 inches
Overall Height:
Between 1.363 inches and 1.403 inches
Overall Width:
Between 1.363 inches and 1.403 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.015 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.015 inches
Distance From Mounting Shoulder To Front Face:
Between 0.878 inches and 0.898 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
17-31 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0 and 80.0 and 180.0 and 215.0 and 298.0
Shell Type:
Split
Connector Locking Method:
Externally threaded shell
Thread Length:
0.635 inches
Thready Qty Per Inch (tpi):
10
Thread Size:
1.125 inches

**Terminal Location:** 

Back single mating end single contact grouping

## NSN 5935-01-603-7316

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Porcelain
Shell Surface Treatment:
Cadmium
ncluded Contact Quantity:
31 single mating end single contact grouping
ncluded Contact Type:
Round socket single mating end single contact grouping
Special Features:
Contacts per m39029/84-509
Color:
Olive drab
Precious Material And Location:
Contact surface gold
Precious Material:
Gold
Test Data Document:
31349-mil-dtl-28840 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Double stub
Specification Data:
31349-mil-dtl-28840/12 government specification
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
4039b0