NSN 5935-01-603-7439

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-603-7439 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.625 inches **Overall Height:** Between 1.488 inches and 1.528 inches **Overall Width:** Between 1.488 inches and 1.528 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.140 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.140 inches **Distance From Mounting Shoulder To Front Face:** Between 0.878 inches and 0.898 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 19-42 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 and 88.0 and 163.0 and 207.0 and 281.0 Shell Type: Split **Connector Locking Method:** Externally threaded shell Thread Length: 0.635 inches Thready Qty Per Inch (tpi): 10 **Thread Size:** 1.312 inches

Terminal Location:

Back single mating end single contact grouping

NSN 5935-01-603-7439

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Porcelain
Shell Surface Treatment:
Cadmium
ncluded Contact Quantity:
42 single mating end single contact grouping
ncluded Contact Type:
Round socket single mating end single contact grouping
Special Features:
Contacts per m39029/84-509
Color:
Olive drab
Precious Material And Location:
Contact surface gold
Precious Material:
Gold
Test Data Document:
31349-mil-dtl-28840 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Double stub
Specification Data:
31349-mil-dtl-28840/12 government specification
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No No
Fiig:
A039b0