

View Online at <https://aerobasegroup.com/nsn/5935-01-604-1314>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, internal coupling

Overall Length:

1.294 inches

Overall Diameter:

1.406 inches

Threaded Device Type:

Back shell

Mating End Quantity:

1

Contact Position Arrangement Style:

17-2 single mating end

Contact Removability:

Removable single mating end all contact groupings

Polarization Method:

Key or multiple key

Insert Position In Deg:

18.0 and 95.0 and 140.0 and 228.0 and 225.0

Shell Type:

Solid

Connector Locking Method:

Bayonet slot

End Application:

B-2

Operating Temperature Rating:

Between -65.0 degrees celsius and 175.0 degrees celsius

Thready Qty Per Inch (tpi):

20

Thread Size:

0.938 inches

Terminal Location:

Back single mating end all contact groupings

Terminal Type:

Crimp single mating end all contact groupings

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium and nickel

Included Contact Quantity:

38 single mating end 2nd contact grouping

Included Contact Type:

Round pin single mating end 2nd contact grouping

Special Features:

Contacts per m39029/58-360 and /90-529

Precious Material And Location:

Contact surface gold

Precious Material:

Gold

Test Data Document:

81349-mil-dtl-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef

Specification Data:

96906-ms27467 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-dtl-38999 spec.