## NSN 5935-01-604-1339

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-604-1339 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, internal coupling **Overall Length:** 1.294 inches **Overall Diameter:** 0.859 inches **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** Aden 9-98 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Key or multiple key **Insert Position In Deg:** 18.0 and 95.0 and 140.0 and 228.0 and 255.0 Shell Type: Solid **Connector Locking Method:** Bayonet slot **End Application:** Fadc Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.438 inches **Terminal Location:** Back single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Nickel

**Included Contact Quantity:** 

3 single mating end single contact grouping

## NSN 5935-01-604-1339

Electrical Plug Connector - Page 2 of 2



Included Contact Type:
Round socket single mating end single contact grouping
Special Features:
Contacts per m39029/56-356
Precious Material And Location:
Contact surface gold
Precious Material:
Gold
Test Data Document:
81349-mil-dtl-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unef
Specification Data:
96906-ms27467 government standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mill of the Williams Of an about No.

Mil-std (military Standard):

Mil-dtl-38999 spec.