NSN 5935-01-604-8781

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-604-8781 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Rectangular shape, insulation piercing **Overall Length:** 1.55 inches **Overall Height:** 0.700 inches **Overall Width:** 0.510 inches **Distance Between Mounting Facility Centers:** 1.310 inches **Threaded Device Type:** Mounting hole **Mating End Quantity: Contact Position Arrangement Style:** "2, 15" single mating end **Contact Maximum Current Rating In Amps:** 3.0 single mating end single contact grouping **Polarization Method:** Mating end **Connector Locking Method:** Screw **End Application:** An/tmq-44 (v) **Operating Tempurature Rating:** Between -55.0 degrees celsius and 105.0 degrees celsius Thready Qty Per Inch (tpi): 40 **Thread Size:** 4.0 inches **Terminal Location:** Back single mating end single contact grouping **Insert Material:** Copper alloy single mating end **Terminal Type:** Quick disconnect, female single mating end single contact grouping **Shell Material:**

Steel

NSN 5935-01-604-8781

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Tin
ncluded Contact Quantity:
15 single mating end single contact grouping
ncluded Contact Type:
Round pin single mating end single contact grouping
Product Name:
Apt, skt save dbis slim m/f
Special Features:
Dielectric withstanding voltage 1000 vac for one minute; mounting screw is 0.55 inches in lenth, head is 0.19 length and thread length is .36
nches; insulator is pbt fiber reinforced (ul 94v-0 rated); hardware is nickel plated
Precious Material And Location:
Contact terminals gold
Precious Material:
Gold
Thread Series Designator:
Jnc
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
A039b0