NSN 5935-01-604-8914

Electrical Bulkhead Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-604-8914 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.289 inches **Overall Height:** 1.239 inches **Overall Width:** Between 1.219 inches and 1.239 inches **Environmental Protection:** Moisture proof and salt water resistant and corrosion resistant and dust resistant and fuel resistant and fungus resistant and humidity resistant and oil resistant and shock resistant **Unthreaded Mounting Hole Diameter:** 0.138 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.969 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.815 inches **Distance From Mounting Shoulder To Front Face:** Between 0.815 inches and 0.820 inches **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** Aubc 15-18 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway Shell Type: Solid **Connector Locking Method:** Bayonet pin Thread Length:

0.219 inches

Operating Tempurature Rating:

Between -65.0 degrees celsius and 200.0 degrees celsius

Features Provided:

Scoopproof design

NSN 5935-01-604-8914

Electrical Bulkhead Connector - Page 2 of 2



Thready Qty Per Inch (tpi):
20
Thread Size:
0.812 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold and silver single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Nickel
Included Contact Quantity:
18 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material:
Gold and silver
Test Data Document:
81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-c-38999 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0