Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-605-0399

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
32.5 millimeters
Overall Diameter:
55.6 millimeters
Distance From Mounting Shoulder To Front Face:
9.9 millimeters
Mounting Facility Thickness:
0.118 millimeters
Threaded Device Type:
Back shell or coupling facility
Mating End Quantity:
Contact Position Arrangement Style:
23-55 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
End Application:
Generalspt
Operating Tempurature Rating:
200.0 degrees celsius
Thread Size:
41.0 millimeters
Thread Pitch In Millimeters:
1.0
Terminal Location:
Back single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum

No

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment: Nickel **Thread Tolerance Class:** 6g external **Included Contact Quantity:** 55 single mating end single contact grouping Included Contact Type: Brush socket single mating end single contact grouping **Product Name:** Jam nut receptable **Special Features:** Suggested operating voltage (sea level) is 600 ac and 850 dc; fully mated indicator is red band **Thread Series Designator:** lso m **Specification Data:** A 81349-dod-c-38999/24 government specification Shelf Life: N/a Unit Of Measure: **Demilitarization:** Fiig: A039b0