## NSN 5935-01-605-0399

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-605-0399 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 32.5 millimeters **Overall Diameter:** 55.6 millimeters **Distance From Mounting Shoulder To Front Face:** 9.9 millimeters **Mounting Facility Thickness:** 0.118 millimeters **Threaded Device Type:** Back shell or coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 23-55 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway Shell Type: Solid **Connector Locking Method:** Externally threaded shell **End Application:** Generalspt **Operating Tempurature Rating:** 200.0 degrees celsius **Thread Size:** 41.0 millimeters **Thread Pitch In Millimeters:** 

1.0 **Terminal Location:** Back single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:** Aluminum

NSN 5935-01-605-0399 Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Nickel
Thread Tolerance Class:
6g external
ncluded Contact Quantity:
55 single mating end single contact grouping
ncluded Contact Type:
Brush socket single mating end single contact grouping
Product Name:
Jam nut receptable
Special Features:
Suggested operating voltage (sea level) is 600 ac and 850 dc; fully mated indicator is red band
Thread Series Designator:
so m
Specification Data:
A 81349-dod-c-38999/24 government specification
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
A039b0