NSN 5935-01-605-2144

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-605-2144

Thread Class:
2b
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape, internal coupling
Overall Length:
36.2 millimeters
Overall Diameter:
35.7 millimeters
Threaded Device Type:
Back shell and coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
17-2 single mating end
Contact Removability:
Removable single mating end all contact groupings
Polarization Method:
Key or multiple key
Insert Position In Deg:
0.0 and 80.0 and 142.0 and 196.0 and 293.0
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling ring
End Application:
B2
Operating Tempurature Rating:
Between -65.0 degrees celsius and 175.0 degrees celsius
Thread Size:
25.0 millimeters and 1.188 inches
Terminal Location:
Back single mating end all contact groupings
Terminal Type:
Crimp single mating end all contact groupings
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Thread Tolerance Class:

6g external

NSN 5935-01-605-2144

Electrical Plug Connector - Page 2 of 2



Included Contact Quantity:
38 single mating end 2nd contact grouping
Included Contact Type:
Triaxial pin single mating end 1st contact grouping
Special Features:
Contacts per m39029/90-529 and /58-360
Color:
Olive drab
Precious Material And Location:
Contact surfaces gold
Precious Material:
Gold
Test Data Document:
81349-mil-dtl-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Iso m and special acme
Specification Data:
81349-mil-dtl-38999/26 government specification
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A039b0