NSN 5935-01-605-7435

Electrical Plug Connector - Page 1 of 2



| Electrical Flug Confilector - Fage 1 of 2 |
|---|
| View Online at https://aerobasegroup.com/nsn/5935-01-605-7435 |
| Body Style: |
| Hood, side opening w/clamp |
| Overall Length: |
| 1.932 inches |
| Overall Height: |
| 2.069 inches |
| Overall Width: |
| 0.567 inches |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 14 single mating end |
| Contact Removability: |
| Removable single mating end single contact grouping |
| Polarization Method: |
| Shell |
| Connector Locking Method: |
| Jackscrew |
| Connector Cable Strain Relief Method: |
| Cable clamp |
| Cable Opening Length: |
| 0.190 inches |
| Cable Opening Width: |
| 0.190 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Terminal Type: |
| Crimp single mating end single contact grouping |
| Shell Material: |
| Aluminum alloy |
| Shell Surface Treatment: |
| Anodize |
| Shell Guide Type And Location Designator: |
| |

Position a pin

Included Contact Quantity:

14 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Special Features:

Contacts per m39029/34-271

Precious Material And Location:

Contac surface gold

NSN 5935-01-605-7435

Electrical Plug Connector - Page 2 of 2



| Gold |
|--|
| Test Data Document: |
| 81349-mil-dtl-28748 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Specification Data: |
| 81349-mil-dtl-28748/3 government specification |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Mil-std (military Standard): Mil-dtl-28748 spec.

Fiig: A039b0

Precious Material: