## NSN 5935-01-605-9551

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-605-9551

**Thread Class:** 

2a and 2a

**Thread Direction:** 

Right-hand and right-hand

**Body Style:** 

Straight shape, external coupling

**Overall Length:** 

2.062 inches

**Overall Height:** 

Between 1.363 inches and 1.403 inches

**Overall Width:** 

Between 1.363 inches and 1.403 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.015 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.015 inches

**Distance From Mounting Shoulder To Front Face:** 

Between 0.878 inches and 0.898 inches

**Threaded Device Type:** 

Back shell and coupling facility

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

17-31 single mating end

**Contact Removability:** 

Removable single mating end single contact grouping

**Polarization Method:** 

Keyway or multiple keyway

Insert Position In Deg:

0.0 and 116.0 and 160.0 and 191.0 and 311.0

Shell Type:

Split

**Connector Locking Method:** 

Externally threaded shell

Thready Qty Per Inch (tpi):

18 and 10

**Thread Size:** 

1.125 inches and 1.125 inches

**Terminal Location:** 

Back single mating end single contact grouping

**Terminal Type:** 

Crimp single mating end single contact grouping

## NSN 5935-01-605-9551

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Included Contact Quantity:
31 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Special Features:
Contact per m39029/84-452
Color:
Olive drab
Precious Material And Location:
Contact surface gold
Precious Material:
Gold
Test Data Document:
81349-mil-dtl-28840 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unef and double stub
Specification Data:
81349-mil-dtl-28840/10 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0