NSN 5935-01-608-2708

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-608-2708 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.349 inches **Overall Height:** 1.219 inches **Overall Width:** 1.219 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.969 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.969 inches **Distance From Mounting Shoulder To Front Face:** 0.820 inches **Threaded Device Type:** Back shell **Mating End Quantity:** 1 **Contact Position Arrangement Style:** Arbq 15-15 single mating end **Contact Removability:** Removable single mating end all contact groupings **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 34.0 and 105.0 and 132.0 and 220.0 and 265.0 Shell Type: **Connector Locking Method:** Bayonet pin **End Application:** B-1 **Operating Tempurature Rating:** Between -65.0 degrees celsius and 175.0 degrees celsius

Thread Size:

0.813 inches

Terminal Location:

Back single mating end all contact groupings

NSN 5935-01-608-2708

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Crimp single mating end all contact groupings
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Included Contact Quantity:
14 single mating end 2nd contact grouping
Included Contact Type:
Round pin single mating end all contact groupings
Special Features:
Contacts per m39029/58-363 and -364
Precious Material And Location:
Contact surfaces gold
Precious Material:
Gold
Test Data Document:
81349-mil-dtl-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unef
Specification Data:
96906-ms27656 government standard
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-dtl-38999 spec.