NSN 5935-01-609-1442

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-609-1442 **Thread Class:** 2a and 2a **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 2.031 inches **Overall Diameter:** 1.193 inches **Unthreaded Mounting Hole Diameter:** 0.630 inches **Distance From Mounting Shoulder To Front Face:** 0.720 inches **Mounting Facility Thickness:** 0.128 inches **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 10s-4 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Key or multiple key **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Externally threaded shell **End Application:** Dragonspear Thready Qty Per Inch (tpi): 24 and 24 **Thread Size:** 0.625 inches and 0.625 inches **Terminal Location:** Back single mating end single contact grouping

Terminal Type: Crimp single mating end single contact grouping

NSN 5935-01-609-1442

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Included Contact Quantity:
2 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Special Features:
Contacts per sae-as39029/45
Color:
Olive drab
Precious Material And Location:
Contact surface gold
Precious Material:
Gold
Thread Series Designator:
Unef and unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-dtl-5015 spec.