

View Online at <https://aerobasegroup.com/nsn/5935-01-609-1442>

**Thread Class:**

2a and 2a

**Thread Direction:**

Right-hand and right-hand

**Body Style:**

Straight shape, external coupling

**Overall Length:**

2.031 inches

**Overall Diameter:**

1.193 inches

**Unthreaded Mounting Hole Diameter:**

0.630 inches

**Distance From Mounting Shoulder To Front Face:**

0.720 inches

**Mounting Facility Thickness:**

0.128 inches

**Threaded Device Type:**

Back shell and coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

10s-4 single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Polarization Method:**

Key or multiple key

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded shell

**End Application:**

Dragonspear

**Thready Qty Per Inch (tpi):**

24 and 24

**Thread Size:**

0.625 inches and 0.625 inches

**Terminal Location:**

Back single mating end single contact grouping

**Terminal Type:**

Crimp single mating end single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium

**Included Contact Quantity:**

2 single mating end single contact grouping

**Included Contact Type:**

Round socket single mating end single contact grouping

**Special Features:**

Contacts per sae-as39029/45

**Color:**

Olive drab

**Precious Material And Location:**

Contact surface gold

**Precious Material:**

Gold

**Thread Series Designator:**

Unef and unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-dtl-5015 spec.