NSN 5935-01-612-1780



Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-01-612-1780 **Thread Class:** 2a and 2a **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 2.500 inches **Overall Height:** 1.500 inches **Overall Width:** 1.500 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.156 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.156 inches **Distance From Mounting Shoulder To Front Face:** 0.750 inches **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 20-19 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Key or multiple key **Insert Position In Deg:** 180.0 Shell Type: **Connector Locking Method:** Externally threaded shell **End Application:** An/blq-10 (v) Thready Qty Per Inch (tpi): 18 and 18

Thread Size:

1.188 inches and 1.250 inches

Terminal Location:

Back single mating end single contact grouping

NSN 5935-01-612-1780

Electrical Receptacle Connector - Page 2 of 2



| Terminal Type: |
|---|
| Crimp single mating end single contact grouping |
| Shell Material: |
| Aluminum alloy |
| Shell Surface Treatment: |
| Cadmium |
| Included Contact Quantity: |
| 3 single mating end single contact grouping |
| Included Contact Type: |
| Round pin single mating end single contact grouping |
| Special Features: |
| Contacts per m39029/44-291 |
| Color: |
| Olive drab |
| Precious Material And Location: |
| Contact surfaces silver |
| Precious Material: |
| Silver |
| Thread Series Designator: |
| Unef and unef |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |
| Mil-std (military Standard): |
| Mil-dtl-5015 spec. |