

View Online at <https://aerobasegroup.com/nsn/5935-01-612-8566>

Body Style:

Straight shape, w/cable seal

Cable Entrance Diameter:

Between 3.5 millimeters and 8.0 millimeters

Mating End Quantity:

1

Contact Maximum Current Rating In Amps:

10.0 single mating end single contact grouping

Connector Locking Method:

Latch

Connector Cable Strain Relief Method:

Cable clamp w/telescoping bushing

End Application:

5895-01-564-7999

Operating Temperature Rating:

Between -30.0 degrees celsius and 80.0 degrees celsius

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Silver single mating end single contact grouping

Insert Material:

Plastic polyamide single mating end

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Zinc alloy

Shell Surface Treatment:

Nickel

Included Contact Quantity:

4 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Special Features:

The rated voltage is 50v. The boot is made from polyurethan.

Precious Material And Location:

Contact plating silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0